



# PERRY JOHNSON LABORATORY ACCREDITATION, INC.

## Certificate of Accreditation

*Perry Johnson Laboratory Accreditation, Inc. has assessed the Laboratory of:*

### ***Interface Performance Materials, Inc. / Lewis Plant***

***9635 Main Street, Beaver Falls, NY 13305***

*(Hereinafter called the Organization) and hereby declares that Organization is accredited in accordance with the recognized International Standard:*

### **ISO/IEC 17025:2005**

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (as outlined by the joint ISO-ILAC-IAF Communiqué dated January 2009):

### ***Testing of Mechanical and Physical Properties of Gasket Materials as Outlined in ASTM F104 and Related Standards***

*(As detailed in the supplement)*

Accreditation claims for such testing and/or calibration services shall only be made from addresses referenced within this certificate. This Accreditation is granted subject to the system rules governing the Accreditation referred to above, and the Organization hereby covenants with the Accreditation body's duty to observe and comply with the said rules.

For PJLA:

Tracy Szerszen  
President/Operations Manager

Perry Johnson Laboratory  
Accreditation, Inc. (PJLA)  
755 W. Big Beaver, Suite 1325  
Troy, Michigan 48084

*Initial Accreditation Date:*

May 15, 2005

*Issue Date:*

June 20, 2015

*Expiration Date:*

August 31, 2015

*Accreditation No.:*

59340

*Certificate No.:*

L15-202

*The validity of this certificate is maintained through ongoing assessments based on a continuous accreditation cycle. The validity of this certificate should be confirmed through the PJLA website: [www.pjllabs.com](http://www.pjllabs.com)*



# Certificate of Accreditation: Supplement

## Interface Performance Materials, Inc. / Lewis Plant

9635 Main Street, Beaver Falls, NY 13305  
Contact: Gregory Peters Phone: 315-346-3251

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical <sup>F</sup>	Gasket Material	Compression/Recovery	ASTM F36 ISI 10-211-009	± 0.1 %
		Fluid Resistance	ASTM F146 ISI 10-211-018 (22 in)	± 0.1 %
		Tension	ASTM F152 ISI 10-211-006	± 0.01 mPa
		Density	ASTM F1315 ISI 10-211-004	± 0.01 g/cm <sup>3</sup>
		Basis Weight	TAPPI T410 ISI 10-211-003	± 1 g/m <sup>2</sup>
		Thickness and Classification	ASTM F104 ISI 10-211-002	± 0.002 5 mm

1. The presence of a superscript F means that the laboratory performs testing of the indicated parameter at its fixed location. Example: Outside Micrometer <sup>F</sup> would mean that the laboratory performs this testing at its fixed location.

